

KVM Selection Guide





Your Solutions for IT Assets and Connectivity Management

ATEN is one of the leading manufacturers and solution providers for connecting your business assets and IT strategies with innovative hardware and software technologies. With more than 40 years of experience in connectivity, accessing, sharing, and management technologies, ATEN is committed to helping your business grow by providing the best-in-class ATEN IT infrastructure management solutions to overcome your challenges.

HDBaseT™ KVM Extenders

Model No.		CE624	CE620	CE611	CE610A
Product					
HDBaseT		HDBaseT 2.0	HDBaseT 2.0	HDBaseT	HDBaseT
Max Resolution / Distance @ Cat 6a		1920 x 1200 @ 100 m / 1080p @ 100 m			
Interface	Unit to Unit	Cat 6 / 6a x 1	Cat 6 / 6a x 1	Cat 6 / 6a x 1	Cat 5e x 1
	Keyboard, Mouse	USB	USB	USB	USB
	Video	DVI-D (Single Link)	DVI-D (Single Link)	DVI-D (Single Link)	DVI-D (Single Link)
HDCP		Compatible	N/A	N/A	Compatible
Dual Display		•	N/A	N/A	N/A
Long Reach Mode		•	•	N/A	• (Passive enable)
Audio		Stereo (Mic in, Speaker out)	Stereo (Mic in, Speaker out)	Stereo (Mic in, Speaker out)	N/A
RS-232 Channel		•	•	•	N/A
Ethernet		N/A	N/A	N/A	N/A
USB Channel		•	•	•	• (40 Mbps)

Model No.		CE924	CE920	CE820
Product				
HDBaseT		HDBaseT 2.0	HDBaseT 2.0	HDBaseT 2.0
Max Resolution / Distance @ Cat 6a		4K @ 100 m / 1080p @ 100 m		
Interface	Unit to Unit	Cat 6 / 6a x 1	Cat 6 / 6a x 1	Cat 6 / 6a x 1
	Keyboard, Mouse	USB	USB	USB
	Video	DisplayPort	DisplayPort	HDMI
HDCP		Compatible	Compatible	HDCP 2.2
Dual Display		•	N/A	N/A
Long Reach Mode		•	•	•
Audio		DisplayPort / Stereo (Mic in, Speaker out)	DisplayPort / Stereo (Mic in, Speaker out)	HDMI / Stereo (Mic in, Speaker out)
RS-232 Channel		•	•	•
Ethernet		N/A	•	•
USB Channel		•	•	•

KVM Extenders

Model No.		CE680 / CE690	CE604	CE600 / CE602
Product				
Max Distance		600 m / 20 km	60 m	60 m
Resolution		CE680: 1920 x 1200 @ 60Hz (600 m) CE690: 1920 x 1200 @ 60Hz (20 km)	1920 x 1200 @ 60Hz (30 m); 1024 x 768 @ 60Hz (60 m)	CE600: 1920 x 1200 @ 60Hz (30 m); CE602: 2560 x 1600 @ 60Hz (40 m, Dual Link)
Interface	Unit to Unit	Fiber optic x 1	Cat 5e x 1 (or 2)	Cat 5e x 1 (or 2)
	Keyboard, Mouse	USB	USB	USB
	Video	DVI-D (Single Link)	DVI-D (Single Link)	CE600: DVI-D (Single Link) CE602: DVI-D (Dual Link)
Audio		Stereo (Mic in, Speaker out)	Stereo (Mic in, Speaker out)	Stereo (Mic in, Speaker out)
RS-232 Channel		•	•	•
Dual View		N/A	•	N/A
USB 2.0 Periperal		N/A	N/A	N/A
USB Touch Panel		•	N/A	N/A
Local Console		•	N/A	N/A

Model No.		CE775	CE770	CE750A	CE700A	CE100	CE350 / CE370	CE250A
Product								
Max Distance		300m	300 m	200 m	150 m	100 m	150 m / 300 m	150 m
Resolution		1920 x 1200 @ 60 Hz (150 m)	1920 x 1200 @ 60Hz (150 m)	1920 x 1200 @ 60Hz (30 m)	1920 x 1200 @ 60Hz (30 m)	1920 x 1200 @ 60 Hz (30 m)	CE350: 1920 x 1200 @ 60Hz (30 m) CE370: 1920 x 1200 @ 60Hz (150 m)	1280 x 1024 @ 60Hz (150 m)
Interface	Unit to Unit	Cat 5e x 2	Cat 5e x 1	Cat 5e x 1	Cat 5e x 1	Cat 5e x 1	Cat 5e x 1	Cat 5e x 1
	Keyboard, Mouse	USB	USB	USB	USB	USB	PS/2	PS/2
	Video	VGA	VGA	VGA	VGA	VGA	VGA	VGA
Audio		Stereo (Mic in, Speaker out)	Stereo (Mic in, Speaker out)	Stereo (Mic in, Speaker out)	N/A	N/A	Stereo (Mic in, Speaker out)	N/A
RS-232 Channel		•	•	•	N/A	N/A	•	N/A
Dual View		•	N/A	N/A	N/A	N/A	N/A	N/A
USB 2.0 Periperal		N/A	N/A	N/A	N/A	N/A	N/A	N/A
USB Touch Panel		N/A	N/A	N/A	N/A	N/A	N/A	N/A
Local Console		•	•	•	•	N/A	•	•

Desktop KVM Switches

Model No.		CM1284	CM1164A	CS724KM	CS1953	CS1964	CS1942DP / CS1944DP	CS1922M / CS1924M	CS1922 / CS1924
Product									
Ports		4	4	4	3	4	2/4	2/4	2/4
Interface	Keyboard, Mouse	USB	USB	USB	USB	USB	USB	USB	USB
	Video	HDMI	DVI	N/A	DisplayPort / USB-C*	DisplayPort / HDMI**	DisplayPort	DisplayPort / HDMI**	DisplayPort
Platform Support		Windows, Linux, Sun, Mac	Windows, Linux, Sun, Mac	Windows	Windows, Linux, Mac	Windows, Linux, Mac	Windows, Linux, Mac	Windows, Linux, Mac	Windows, Linux, Mac
USB Hub built in		• (USB 2.0 Type A)	• (USB 2.0 Type A)	•	• (USB 3.1 Gen 1)	• (USB 3.1 Gen 1)	•	• (USB 3.1 Gen 1)	• (USB 3.1 Gen 1)
Audio		•	•	• (Speakers)	•	•	•	•	•
Independent Switching		•	•	•	•	•	•	•	•
Video DynaSync™		•	•	N/A	N/A	•	N/A	N/A	N/A
Dual Display		•	N/A	N/A	N/A	•	•	•	N/A
3D Support		N/A	N/A	N/A	N/A	N/A	•	N/A	N/A

Note: * USB-C transfers video, audio, and data.
** The HDMI port is located in the console section at the back of the switch.


Model No.		CS1912 / CS1914	CS782DP	CS1842 / CS1844	CS1822 / CS1824	CS1792 / CS1794	CS1642A / CS1644A	CS1782A / CS1784A	CS1762A / CS1764A	CS1742 / CS1744
Product										
Ports		2/4	2	2/4	2/4	2/4	2/4	2/4	2/4	2/4
Interface	Keyboard, Mouse	USB	USB	USB	USB	USB	USB	USB	USB	USB
	Video	DisplayPort	DisplayPort	HDMI	HDMI	HDMI	DVI (Dual Link)	DVI (Dual Link)	DVI	VGA (SPHD)
Platform Support		Windows, Linux, Mac	Windows, Linux, Mac, Sun	Windows, Linux, Mac	Windows, Linux, Mac	Windows, Linux, Mac	Windows, Linux, Mac, Sun	Windows, Linux, Mac, Sun	Windows, Linux, Mac, Sun	Windows, Linux, Mac, Sun
USB Hub built in		• (USB 3.1 Gen 1)	N/A	• (USB 3.1 Gen 1)	• (USB 3.1 Gen 2)	•	•	•	•	•
Audio		• (Speakers)	• (Speakers)	•	•	•	•	• (7.1) (CS1782A) • (CS1784A)	•	•
Independent Switching		•	•	•	•	•	•	•	•	•
Video DynaSync™		N/A	N/A	•	N/A	•	•	•	•	N/A
Dual Display		N/A	N/A	•	N/A	N/A	•	N/A	N/A	•
3D Support		N/A	N/A	N/A	N/A	N/A	•	•	N/A	N/A

Model No.		CS1732B / CS1734B	CS1732A / CS1734A	CS82U / CS84U	CS72U / CS74U	CS82A / CS84A	CS74E
Product							
Ports		2/4	2/4	2/4	2/4	2/4	4
Interface	Keyboard, Mouse	PS/2, USB	PS/2, USB	PS/2, USB	USB	PS/2	PS/2
	Video	VGA (SPHD)	VGA (SPHD)	VGA (SPHD)	VGA (SPHD)	VGA	VGA (SPHD)
Platform Support		Windows, Linux, Mac, Sun	Windows, Linux, Mac, Sun	Windows, Linux, Mac, Sun	Windows, Linux, Mac, Sun	Windows, Linux	Windows, Linux
USB Hub built in		•	•	N/A	N/A	N/A	N/A
Audio		•	•	N/A	•	N/A	N/A
Independent Switching		•	•	N/A	N/A	N/A	N/A
Video DynaSync™		•	N/A	•	N/A	N/A	N/A

Rack KVM Switches

Model No.		CS19208 / CS19216	CS18208 / CS18216	CS1798 / CS17916	CS1768 / CS1788	CS1308 / CS1316	CS1708A / CS1716A
Product							
Port Selection		OSD, Hotkey, Pushbutton, RS-232 commands	OSD, Hotkey, Pushbutton, RS-232 commands	OSD, Hotkey, Pushbutton	OSD, Hotkey, Pushbutton	OSD, Hotkey, Pushbutton	OSD, Hotkey, Pushbutton
Ports		8/16	8/16	8/16	8	8/16	8/16
Interface	Keyboard, Mouse	USB	USB	USB	USB	PS/2, USB	PS/2, USB
	Video	HDMI, DisplayPort	HDMI	HDMI	CS1768: DVI (Single Link), VGA CS1788: DVI (Dual Link) , VGA	VGA	VGA
Expansion		128/256 (via Cascade)	512/256 (via Cascade)	512/256 (Cascade)	512 (Cascade)	64/256 (Cascade)	256/512 (Daisy-chain)
Resolution		4096 x 2160 @ 60Hz	4096 x 2160 @ 60Hz	1920 x 1080 @ 60Hz; 1920 x 1200 @ 60Hz	2560 x 1600 @ 60Hz; 1920 x 1200 @ 60Hz	2048 x 1536; DDC2B	2048 x 1536; DDC2B
Platform Support		Windows, Linux, Sun, Mac	Windows, Linux, Sun, Mac	Windows, Linux, Mac, Sun	Windows, Linux, Mac, Sun	Windows, Linux, Mac, Sun	Windows, Linux, Mac, Sun
Audio		• (Speakers)	• (Speakers)	• (Speakers)	•	N/A	N/A
USB Peripheral Port		• (USB 3.0)	• (USB 3.0)	•	•	N/A	•
Video DynaSync™		•	•	•	•	•	•

Cable KVM Switches

Model No.		CV211	CS62KM	CS22DP	CS22H	CS692	CS682	CS22D
Product								
Ports		1	2	2	2	2	2	2
Interface	Keyboard, Mouse	USB	USB	USB	USB	USB	USB	USB
	Video	VGA	N/A	DisplayPort	HDMI	HDMI	DVI	DVI
Platform Support		Windows, Linux	Windows, iOS, Android, macOS, Linux	Windows, Linux, Mac	Windows, Linux, Mac	Windows, Linux, Mac	Windows, Linux, Mac, Sun	Windows, Linux, Mac, Sun
Audio		N/A	•	•	•	•	•	N/A
Cable Length		CV211 to laptop: 1.8 m CV211 to PC: 0.4 m	1.2 m	1.2 m	1.2 m	1.2 m	1.2 m	1.2 m
USB Peripheral Sharing		N/A	N/A	•	•	•	•	•
Video DynaSync™		N/A	N/A	N/A	N/A	•	•	N/A

Model No.		CS62U / CS62US	CS64U / CS64US	CS22U	CS62S	CS62A	CS64A
Product							
Ports		2	4	2	2	2	4
Interface	Keyboard, Mouse	USB	USB	USB	PS/2	PS/2	PS/2
	Video	VGA	VGA	VGA	VGA	VGA	VGA
Platform Support		Windows, Linux, Mac, Sun	Windows, Linux, Mac, Sun	Windows, Linux, Mac, Sun	Windows, Linux	Windows, Linux	Windows, Linux
Audio		•	•	N/A	N/A	•	•
Cable Length		1.8 m (CS62U) 0.9 m (CS62US)	1.8 m (CS64U) 0.9 m, 1.2 m (CS64US)	0.9 m	0.9 m	1.2 m	1.8 m
USB Peripheral Sharing		•	•	•	N/A	N/A	N/A
Video DynaSync™		•	•	N/A	N/A	N/A	N/A

LCD Consoles

Model No.		CL3800	CL3700	CL3100	CL6700	CL3000	CL5800	CL1000
Product								
Size		CL3800NW: 18.5"	CL3700NW: 18.5"	CL3100NX: 18.5"	CL6700MW: 17.3"	CL3000N: 19"	CL5800N: 19"	CL1000M: 17" CL1000N: 19"
Interface	KB/Mouse	USB	USB	USB	USB	PS/2-USB	PS/2-USB	PS/2
	Video	HDMI, DVI-D, VGA	HDMI	VGA	HDMI, DVI-D, VGA	VGA	VGA	VGA
Second Console		USB, HDMI, DVI-D, HDB-15	USB, HDMI	USB, HDB-15	USB, HDMI, DVI-D, HDB-15	PS/2, USB, HDB-15	PS/2, USB, HDB-15	N/A
Platform Support		Windows, Linux, Mac, Sun	Windows, Linux, Mac, Sun	Windows, Linux, Mac, Sun	Windows, Linux, Mac, Sun	Windows, Linux, Mac, Sun	Windows, Linux, Mac, Sun	Windows, Linux
Single Rail / Dual Rail		Dual Rail	Single Rail	Single Rail	Single Rail	Single Rail	Dual Rail	Single Rail

LCD KVM Switches

Model No.		CL6708	CL1308 / CL1316	CL3108 / CL3116	CL5808 / CL5816	CL5708 / CL5716	CL1008 / CL1016
Product							
Size		CL6708MW: 17.3"	CL1308N / CL1316N: 19"	CL3108NX / CL3116NX: 18.5"	CL5808N / CL5816N: 19"	CL5708M / CL5716M: 17" CL5708N / CL5716N: 19"	CL1008M / CL1016M: 17"
Ports		8	8/16	8/16	8/16	8/16	8/16
Interface	KB/Mouse	USB	PS/2-USB	PS/2-USB	PS/2-USB	PS/2-USB	PS/2
	Video	DVI-I	VGA	VGA	VGA	VGA	VGA
Expansion		64 (Cascade)	128/256 (Cascade)	128/256 (via Cascade)	256/512 (Daisy-chain)	256/512 (Daisy-chain)	128/256 (Daisy-chain)
Second Console		USB, DVI-I	N/A	N/A	PS/2, USB, HDB-15 (SPHD)	PS/2, USB, HDB-15 (SPHD)	N/A
Platform Support		Windows, Linux, Mac, Sun	Windows, Linux, Mac, Sun	Windows, Linux, Sun, Mac	Windows, Linux, Mac, Sun	Windows, Linux, Mac, Sun	Windows, Linux
KVM over IP		N/A	N/A	N/A	N/A	N/A	N/A
Single Rail / Dual Rail		Single Rail	Single Rail	Single Rail	Dual Rail	Single Rail	Single Rail

Model No.		CL5708I / CL5716I	KL1508A / KL1516A	KL1108V / KL1116V	KL1508AI / KL1516AI
Product					
Multiple Sessions	Local	1 (Share)	1	1	1 (Share)
	Remote		N/A	1	
Size		CL5708IM / CL5716IM: 17" CL5708IN / CL5716IN: 19"	KL1508AM / KL1516AM: 17" KL1508AN / KL1516AN: 19"	KL1108VN / KL1116VN: 19"	KL1508AIM / KL1516AIM: 17" KL1508AIN / KL1516AIN: 19"
Ports		8/16	8/16	8/16	8/16
Computer	Connector	SPHD-17	RJ-45	RJ-45	RJ-45
	Support Interface	PS/2, USB, VGA	PS/2, USB, VGA; HDMI; DisplayPort; Sun Legacy; Serial; DVI-D	PS/2, USB, VGA; HDMI; DisplayPort; Sun Legacy; Serial; DVI-D	PS/2, USB, VGA; HDMI; DisplayPort; Sun Legacy; Serial; DVI-D
	Support Platform	Windows, Linux, Mac, Sun	Windows, Linux, Mac, Sun	Windows, Linux, Mac, Sun	Windows, Linux, Mac, Sun
Expansion		128/256 (Daisy-chain)	256/512 (Daisy-chain)	128/256 (Cascade)	128/256 (Daisy-chain)
Second Console		PS/2, USB, HDB-15 (SPHD)	PS/2, USB, HDB-15	USB, DVI, HDB-15	PS/2, USB, HDB-15
KVM over IP		•	N/A	•	•
Single Rail / Dual Rail		Single Rail	Dual Rail	Dual Rail	Dual Rail

Secure KVM

Model No.	CS1182DP	CS1184DP	CS1188DP	CS1142DP	CS1144DP	CS1148DP
Product						
Ports	2	4	8	2	4	8
PC Video Connector	DisplayPort					
Console Video Connector	HDMI					
Number of Displays	Single Display			Dual Display		
Resolution	Max. 3840 x 2160 @ 30Hz (UHD)					
Console Keyboard, Mouse Interface	PS/2, USB					
CAC Port	Yes					
Audio	Analog Speaker Only					

Model No.	CS1182H	CS1184H	CS1188H	CS1142H	CS1144H	CS1148H
Product						
Ports	2	4	8	2	4	8
PC Video Connector	HDMI					
Console Video Connector	HDMI					
Number of Displays	Single Display			Dual Display		
Resolution	Max. 3840 x 2160 @ 30Hz (UHD) 1920 x 1080 (FHD)					
Console Keyboard, Mouse Interface	PS/2, USB					
CAC Port	Yes					
Audio	Analog Speaker Only					

Model No.	CS1182D	CS1184D	CS1188D	CS1142D	CS1144D	CS1148D
Product						
Ports	2	4	8	2	4	8
PC Video Connector	DVI					
Console Video Connector	DVI					
Number of Displays	Single Display			Dual Display		
Resolution	3840 x 2160 @ 30Hz*, DVI Dual Link: 2560 x 1600; DVI Single Link: 1920 x 1200; DVI-A: 2048 x 1536					
Console Keyboard, Mouse Interface	PS/2, USB					
CAC Port	Yes					
Audio	Analog Speaker Only					

Note: * DVI Secure KVM Switches offer up to 3840 x 2160 @ 30Hz video output on compatible HDMI-interfaced monitors/computers with ATEN DVI-to-HDMI KVM cables.

Corporate Headquarters

ATEN International Co., Ltd.

3F, No. 125, Sec. 2, Datung Rd., Sijhih District,
New Taipei City 221, Taiwan
Phone: +886-2-8692-6789 Fax: +886-2-8692-6767
<https://www.aten.com/global/en/>
E-mail: marketing@aten.com

America Region:

ATEN Technology Inc.

15365 Barranca Parkway, Irvine, CA 92618, U.S.A.
Phone: +1-949-428-1111 Fax: +1-949-428-1100
<https://www.aten.com/us/en/>
E-mail: sales@aten-usa.com

EMEA Region:

ATEN Infotech N.V.

Mijnwerkerslaan 34, 3550 Heusden-Zolder, Belgium
Phone: +32-11-53-15-43 Fax: +32-11-53-15-44
<https://www.aten.com/eu/en/>
E-mail: sales@aten.be

ATEN U.K. Limited

466 Malton Avenue, Slough SL1 4QU, U. K.
Phone: +44-1753-539-121 Fax: +44-1753-215-253
<https://www.aten.com/gb/en/>
E-mail: sales@aten.co.uk

ATEN Poland Sp. z o. o.

2 Gottlieb Daimler Street, 02-460 Warsaw, Poland
Phone: +48-514-120-220
<https://www.aten.com/pl/pl/>
E-mail: poland@aten.com

ATEN Romania S.R.L.

10 Bucuresti-Nord Road, Global City Business Park,
Building O 13, 6th floor, Voluntari, Ilfov County, Romania
Phone: +40-314-257-746
<https://www.aten.com>
E-mail: romania@aten.com

ATEN Russia Rep. Office

Zolotaya Ulitsa, 11, Moscow, Russia Federation, 105094
BC "ZOLOTO" Office 1A12
Phone: +7-495-134-2808
<https://www.aten.com/ru/ru/>
E-mail: russia@aten.com

ATEN Info Iletisim Ltd.

Beştepe Mah.Yaşam Cad., Neoroma Is Merkezi 13-A / 76
Yenimahalle Ankara, Turkey
Phone: +90-312-284-0027
<https://www.aten.com>
E-mail: turkey@aten.com

Oceania Region:

ATEN ANZ Pty Ltd.

Suite 2, Level 1, Tower 2,
394 Lane Cove Road, Macquarie Park NSW 2113, Australia
Phone: +61-2-9114-9933 Fax: +61-2-8072-3723
<https://www.aten.com/au/en/>
E-mail: sales@au.aten.com

Asia Pacific Region:

ATEN China Co., Ltd.

Beijing Headquarters

18/F, Tower A, Horizon International Tower, No.6,
Zhichun Road, Haidian District, Beijing 100088, China
Phone: +86-10-5225-0110 Fax: +86-10-8296-1318
<https://www.aten.com/cn/zh/>
E-mail: sales@aten.com.cn

Shanghai Branch

18E, Shanghai Industrial Investment Building, No. 18
Cao Xi Bei Road, Xuhui District, Shanghai 200030, China
Phone: +86-21-3126-0110 Fax: +86-21-3126-0110-310
<https://www.aten.com/cn/zh/>
E-mail: sales@aten.com.cn

Guangzhou Branch

Room 3913, Ren-Feng Building, No. 490
Tian He Road, Tian He District, Guangzhou 510620, China
Phone: +86-20-3883-0110 Fax: +86-20-3835-0810
<https://www.aten.com/cn/zh/>
E-mail: sales@aten.com.cn

ATEN Japan Co., Ltd.

Tokyo Headquarters

ATEN Bldg. 8-4, Minami-senju 3-chome, Arakawa-ku,
Tokyo 116-0003, Japan
Phone: +81-3-5615-5810 Fax: +81-3-3891-3810
<https://www.aten.com/jp/ja/>
E-mail: sales@atenjapan.jp

Osaka Branch

Awajimachi Dai-Building 3F
3-1-9, Awajimachi, Chuo-ku, Osaka-shi 541-0047, Japan
Phone: +81-6-6229-5810 Fax: +81-6-6229-8810
<https://www.aten.com/jp/ja/>
E-mail: sales@atenjapan.jp

Kyushu Office

Hakataekimaefujii Building 2F, 3-10-24 Hakataeki Mae Hakata-ku,
Fukuoka-shi, Fukuoka-ken 812-0011, Japan
Phone: +81-92-476-5810 Fax: +81-92-476-581
<https://www.aten.com/jp/ja>
E-mail: sales@atenjapan.jp

Nagoya Office

Nishiki Maruemu Building 3F, 3-1-30, Nishiki, Naka Ku,
Nagoya Shi, Aichi Ken, 460-0003, Japan
Phone: +81-52-201-5810 Fax: +81-52-201-5811
<https://www.aten.com/jp/ja>
E-mail: sales@atenjapan.jp

ATEN Korea Co., Ltd.

Seoul Headquarters

B-303, 32, Digital-ro 9-gil,
Geumcheon-gu, Seoul 08512, Korea
Phone: +82-2-467-6789 Fax: +82-2-467-9876
<https://www.aten.com/kr/ko/>
E-mail: sales@aten.co.kr

Busan Branch

1111, 99, Centum dong-ro, Haeundae-gu, Busan 48059, Korea
Phone: +82-51-782-7156 Fax: +82-51-782-7157
<https://www.aten.com/kr/ko/>
E-mail: roy@aten.co.kr

Atech Peripherals, Inc.

New Taipei Headquarters

6F, No.133, Sec. 2, Datung Rd., Sijhih District,
New Taipei City 221, Taiwan
Phone: +886-2-8692-6969 Fax: +886-2-8692-6926
<https://www.aten.com/tw/zh/>
E-mail: taiwan@aten.com

Atech Kaohsiung Office

37F-1A, No. 38, Xinguang Rd., Lingya Dist.,
Kaohsiung City 802, Taiwan
Phone: +886-7-286-8188 Fax: +886-7-286-8199
<https://www.aten.com/tw/zh/>
E-mail: taiwan@aten.com

ATEN Advance Pvt. Ltd.

Address: 2nd Floor, 67, Sudev Complex, Kariappa Road,
Basavanagudi, Bengaluru- 560004, Karnataka, India
Phone: +91-80-4851-7231
<https://www.aten.com>
E-mail: sales@aten.co.in

Africa Region:

ATEN South Africa.

111 10th Road, Block A, first floor, Hyde Park Investment Place,
Sandton, 2196
Phone: +27 67 280 2482
<https://www.aten.com>
E-mail: benjipienaar@aten.com.tw

About ATEN

ATEN International Co., Ltd., established in 1979, is the leading provider of AV/IT connectivity and management solutions. Offering integrated KVM, professional AV, and intelligent power solutions, ATEN products connect, manage, and optimize AV/IT equipment in corporate, government, education, broadcasting and media, and transportation environments. ATEN has 630+ issued international patents and a global R&D team that produces a constant stream of innovative solutions, resulting in a comprehensive portfolio of products available worldwide.

